

TYRE CHANGERS

WHEEL SERVICE EQUIPMENT



BRIGHT LC887N

Features:

- Semi-automatic tilt type tyre changer for cars and light commercials.
- Handles rim sizes up to 26" diameter.
- Pneumatically operated tilt-back column and mounting post lock.
- Self centring 4 jaw turntable with 80mm cylinders for secure wheel clamping.
- Powerful, responsive bead breaker with easily positioned blade.
- Control pedal assembly with step-move functionality.
- Built-in tyre inflator.
- Covered turntable plus jaw and tool head inserts for alloy rim protection.

Standard Accessories:

- Tyre lever.
- Jaw / tool head inserts.

Options:

- AL320 fitting assistor for low profile / run-flat tyres.
- ZD03 leverless tool head adaptor.
- Motorcycle adaptors.
- Plastic tool head.



Technical Specifications:

Inner Clamping Range	13" - 26"
Outer Clamping Range	11" - 24"
Max. Wheel Assembly Diameter	1100 mm
Max. Wheel Assembly Width	355 mm
Turntable Speed	6.5 rpm
Bead Breaking Force	1200 kgf / 12 kN
Motor Rating	1.1 kW / 1.5 hp
Power Supply	230VAC (1 phase)
Pneumatic Supply	8 - 12 bar
Dimensions (W x D x H)	1500 x 1950 x 2050 mm
Mass	255 kgs

TYRECARE LTD

Killeshandra, Co. Cavan, Ireland • Tel. +353 49 433 4486
sales@tyrecare.ie • www.tyrecare.ie