

TYRE CHANGERS

WHEEL SERVICE EQUIPMENT



BRIGHT LC890N



Features:

- Swing type tyre changer for cars and light commercials.
- Handles rim sizes up to 26" diameter.
- Manual swing and mounting post lock.
- Self centring 4 jaw turntable with 80mm cylinders for secure wheel clamping.
- Powerful, responsive bead breaker with easily positioned blade.
- Built-in tyre inflator.
- Covered turntable plus jaw and tool head inserts for alloy rim protection.

Standard Accessories:

- Tyre lever.
- Jaw / tool head inserts.

Options:

- AL330B fitting assistor for low profile / run-flat tyres.
- Motorcycle adaptors.
- Plastic tool head.



Technical Specifications:

Inner Clamping Range	13" - 26"
Outer Clamping Range	11" - 24"
Max. Wheel Assembly Diameter	1250 mm
Max. Wheel Assembly Width	355 mm
Turntable Speed	6.5 rpm
Bead Breaking Force	1000 kgf / 10 kN
Motor Rating	1.1 kW / 1.5 hp
Power Supply	230VAC (1 phase)
Pneumatic Supply	8 - 12 bar
Dimensions (W x D x H)	1350 x 1300 x 1960 mm
Mass	239 kgs

TYRECARE LTD

Killeshandra, Co. Cavan, Ireland • Tel. +353 49 433 4486
sales@tyrecare.ie • www.tyrecare.ie