

## MEDIUM DUTY TRUCK TYRE CHANGER

Designed for professional tyre shops

- The compact tyre changer with double reinforced frame for rims of 12 – 32": ideal for tyre shops for mounting and demounting truck, bus, agricultural vehicle and earthmover tyres
- Rugged chuck design

- Mobile control unit with switch to control two operations simultaneously
- 2 Chuck speeds, preset via switch
- Quick fit aluminium protectors to avoid rim damaging
- Quick lock/unlock system allows faster tool rotation

| Truck Tyre Changers                 | KING 5610           |
|-------------------------------------|---------------------|
| Rim clamping range                  | 14 – 32 inch        |
| Rim clamping range incl. extensions | 32 - 56 inch        |
| Max. wheel width                    | 32"/800 inch/mm     |
| Max. wheel diameter                 | 92.56 /2350 inch/mm |
| Max. wheel weight                   | 1500 kg             |
| Bead braking force                  | 33 kN               |
| Chuck speed                         | 4/8 UpM             |
| Chuck motor rating                  | 1.3 - 18 kW         |
| Hydraulic motor rating              | 1.5 kW              |
| Dimensions (W x D x H) approx.      | 1800x2000x930 mm    |
| Weight                              | 761 kg              |
| Power supply                        | 400 V 3ph 50 Hz     |



## ROBOTIC MEDIUM DUTY TYRE CHANGER

Designed for professional tyre shops

- The compact tyre changer with double reinforced frame and hydraulic control, for rims of 12 – 32": ideal for tyre shops for mounting and demounting truck, bus, agricultural vehicle and earthmover tyres
- Hydraulically controlled tool holder and chuck arm
- Automatically rotating tool

- Control panel mounted on a swing for more comfortable operations
- Hydraulic sidewise movement of the toolholder arm for faster operation
- Quick fit aluminium protectors to avoid rim damaging

| Truck Tyre Changers                 | KING 5610R          |
|-------------------------------------|---------------------|
| Rim clamping range                  | 14 – 32 inch        |
| Rim clamping range incl. extensions | 32 - 56 inch        |
| Max. wheel width                    | 43/1100 inch/mm     |
| Max. wheel diameter                 | 92.56 /2350 inch/mm |
| Max. wheel weight                   | 1500 kg             |
| Bead braking force                  | 33 kN               |
| Chuck speed                         | 4/8 UpM             |
| Chuck motor rating                  | 1.3 - 18 kW         |
| Hydraulic motor rating              | 1.5 kW              |
| Dimensions (W x D x H) approx.      | 1800x2000x930 mm    |
| Weight                              | 897 kg              |
| Power supply                        | 400 V 3ph 50 Hz     |

