

UT-AC1994

AIRCAT IMPACT WRENCH

1" DRV - SUPER DUTY (LONG)

The **Aircat UT-AC1994** is a heavy-duty 1" drive pneumatic impact wrench built for extreme commercial vehicle maintenance. Featuring an 8" extended anvil and 2,500 ft-lb of loosening torque, it effortlessly reaches and seats or removes stubborn lug nuts on trucks, agricultural machinery, and heavy plant equipment with ease.



TECHNICAL DATA

Maximum Torque (ft-lbs):	2300	Length (in.):	26
Loosening Torque (ft-lbs):	2500	Vibration Levels (m/sec2):	9.6
Impacts Per Minute (IPM):	1100	Noise Levels d(B)A:	109
Free Speed (RPM):	4500	Air Consumption (CFM):	16
Square Drive (in.):	1 x 8	Air Inlet (NPT/BSP)(in.):	1/2
Bolt Capacity (in.):	1-1/4	Rec. Hose Size (in.):	1/2
Weight (lbs.):	35	Manufacturer Warranty:	2-Year

TYRECARE LTD

Killeshandra, Co. Cavan, Ireland, H12V309 • Tel. +353 49 433 4486

sales@tyrecare.ie | tyrecarelimited | www.tyrecare.ie



UT1600-TH-A

AIRCAT IMPACT WRENCH

3/4 DRV - PISTOL, COMPOSITE

Aircat UT1600-TH-A

is a high- performance
3/4" drive pneumatic impact
wrench designed for commercial
garages and fleet maintenance.
Combining a lightweight composite body with
quiet exhaust technology, it delivers maximum
breaking power while reducing operator
fatigue on heavy automotive and transport
machinery.



TECHNICAL DATA

Maximum Torque (ft-lbs):	1400	Length (in.):	9.25
Loosening Torque (ft-lbs):	1600	Vibration Levels (m/sec2):	7.4
Impacts Per Minute (IPM):	900	Noise Levels d(B)A:	86
Free Speed (RPM):	4500	Air Consumption (CFM):	10
Square Drive (in.):	3/4	Air Inlet (NPT/BSP)(in.):	3/8
Bolt Capacity (in.):	7/8	Rec. Hose Size (in.):	1/2
Weight (lbs.):	8.1	Manufacturer Warranty:	2-Year

TYRECARE LTD

Killeshandra, Co. Cavan, Ireland, H12V309 • Tel. +353 49 433 4486

sales@tyrecare.ie |  tyrecarelimited |  www.tyrecare.ie



UT1150

AIRCAT IMPACT WRENCH

1/2" DRV - PISTOL, COMPOSITE

Aircat UT1150 is a compact, high-torque 1/2" drive composite air impact wrench built for daily automotive and garage servicing. Ideal for rapid wheel nut and suspension bolt removal, its twin hammer design and quiet operation provide maximum efficiency and comfort in any workshop.



TECHNICAL DATA

Maximum Torque (ft-lbs):	900	Length (in.):	7.5
Loosening Torque (ft-lbs):	1295	Vibration Levels (m/sec2):	8.1
Impacts Per Minute (IPM):	1400	Noise Levels d(B)A:	86
Free Speed (RPM):	9000	Air Consumption (CFM):	8
Square Drive (in.):	1/2	Air Inlet (NPT/BSP)(in.):	1/4
Bolt Capacity (in.):	9/16	Rec. Hose Size (in.):	3/8
Weight (lbs.):	4.5	Manufacturer Warranty:	2-Year

TYRECARE LTD

Killeshandra, Co. Cavan, Ireland, H12V309 • Tel. +353 49 433 4486

sales@tyrecare.ie |  tyrecarelimited |  www.tyrecare.ie

