

KI-1636

KUANI IMPACT WRENCH

3/4" DRV - PISTOL, COMPOSITE

Kuani KI-1636

is a super-duty 3/4 composite air impact wrench built for demanding workshop and industrial applications across Ireland. Delivering up to 1,300 ft-lb (1,763 Nm) of reverse torque, this high-performance pneumatic wrench features a New Twin Hammer clutch mechanism and 3 positive forward power settings with full power in reverse.



TECHNICAL DATA

Square Drive:	3/4-in.	Avg. Air Consumption:	6.7 CFM / 190 L/min
Working Torque at 5th Sec:	1300 ft-lb / 1763 Nm	Air Inlet:	3/8-in.
Free Speed:	6500 RPM	Rec. Hose Size I.D.:	1/2 in.
Torque Transmission Mechanism:	Twin Hammer Clutch	Sound Pressure:	99.1 d(B)A
Power Settings:	3 Forward Settings; Full Power in Reverse	Sound Power:	110.09 d(B)B
Weight:	8.58 lbs. / 3.89 kg	Vibration Levels:	10.7 (m/sec2)
Overall Length:	8.9-in. / 225 mm	Exhaust Type:	Rear exhaust with muffler
Recommended Air Pressure:	90 psi / 6.2 bar		

TYRECARE LTD

Killeshandra, Co. Cavan, Ireland, H12V309 • Tel. +353 49 433 4486

sales@tyrecare.ie |  tyrecarelimited |  www.tyrecare.ie

