TYRE CHANGERS

WHEEL SERVICE EQUIPMENT

BRIGHT LC588S



Concentrate on truck tire service for 15 years, non-stop improving and updating, Now it becomes professional equipment for truck and bus tires. Lifting Arm Featuring a center-supported cylinder for even pressure distribution, this heavy-duty, reinforced steel lifting arm and base includes an integrated safety device to ensure maximum strength and secure operation.

- Movable Operating Unit: Allows full visibility during operation to prevent hazards resulting from operator error.
- Electric Cabinet: adopts CE-level protection standards.
- Reducer: A lightweight, high-strength die-cast aluminium gearbox featuring a sleek design and superior sealing performance.

TECHNICAL DATA

Rim Diameter:	14" - 26" inch	Main Shaft Motor Power:	1.8 kW / 380 VAC / 3hp / 50 hz
Rim width:	1000 mm	Dimensions (W x D x H):	2180 x 2100 x 1200 mm
Max. Wheel Diameter:	1600 mm	Sound Level:	< 75 dB
Hydraulic Power:	130 - 150 bar	Weight:	560 kg
Hydraulic Station Motor Power:	1.5 kW 380 VAC/3hp / 50 hz		

* Optional Accessories: Tyre press roller, Aluminum magnesium alloy protective sleeve

TYRECARE LTD
Killeshandra, Co. Cavan, Ireland, H12V309 • Tel. +353 49 433 4486
sales@tyrecare.ie | tyrecarelimited | www.tyrecare.ie